

**Replacement Listing of Claims
for the Amendment filed December 19, 2005**

Amended Claims

21. (Amended) An adhesive tape assembly in the form of a roll, comprising:
- a double-sided adhesive tape comprising:
 - a front adhesive side comprising a heat-activated adhesive layer of a polyolefin heat-activated adhesive, and
 - a back adhesive side comprising a pressure-sensitive adhesive layer of a pressure-sensitive adhesive; and
 - a release liner comprising:
 - a front liner side comprising a release layer in contact with, bonded to and removable from said pressure-sensitive adhesive layer, and
 - a back liner side comprising a roll stability layer which contacts said heat-activated adhesive layer, said roll stability layer having a contact surface which has a coefficient of friction, when measured against said heat-activated adhesive layer, which provides an increase in roll stability to said adhesive tape assembly when formed into a roll,
- said roll having[[],] a width, an outer circumferential edge, and a diameter that is at least about 20 times said width, wherein said roll [[and]] does not fall apart when held suspended along said outer circumferential edge.
22. (Amended) A release liner in combination with a double-sided adhesive tape, said release liner comprising:
- a front liner side comprising a release layer having a first exposed contact surface bondable to and removable from a pressure sensitive adhesive layer of said double-sided adhesive tape, said release layer comprising a polyolefin homopolymer; and
 - a back liner side comprising a roll stability layer having a second exposed contact surface for contacting a heat activated adhesive layer of said double-sided adhesive tape when said double-sided adhesive tape is in roll form, said roll stability layer comprising an ethylene vinyl acetate.

35. (Amended) A release liner in combination with a double-sided adhesive tape, said release liner comprising:

a front liner side comprising a release layer having a first exposed contact surface bondable to and removable from a pressure sensitive adhesive layer of said double-sided adhesive tape, said release layer comprising a low density polyethylene, a linear low density polyethylene, or an ultra-low density polyethylene; and

a back liner side comprising a roll stability layer having a second exposed contact surface for contacting a heat activated adhesive layer of said double-sided adhesive tape when said double-sided adhesive tape is in roll form, said roll stability layer comprising an ethylene vinyl acetate.

47. (Amended) A roll stable liner for use with a double-sided adhesive tape, said liner comprising:

a front liner side having a first exposed contact surface comprising a polyolefin homopolymer bondable to and removable from a pressure sensitive adhesive layer; and

a back liner side comprising a roll stability layer having a second exposed contact surface for contacting a heat activated adhesive layer, said roll stability layer comprising an ethylene vinyl acetate and up to about 5% by weight of an anti-blocking agent based on the amount of ethylene vinyl acetate present.

54. (Cancelled)

55. (New) The adhesive tape assembly as set forth in claim 21, wherein said pressure-sensitive adhesive layer comprises an acrylic pressure-sensitive adhesive, said heat-activated adhesive layer comprises an olefinic material, said release layer comprises at least one polyolefin, and said roll stability layer comprising an ethylene vinyl acetate.